



- Cabinet system for individual installations of control components, fieldbus modules and other electronics
- Can be combined with control enclosures and industrial PCs
- By default, door at the front, bolted rear panel, other versions optional

Included in delivery

Standard version with door at the front, screwed rear panel, 2 fixed shelves;
Special version customized according to requirements

Technical Data

Enclosure body:

Steel cabinet with door at the front and screwed rear panel

Dimensions: 600 x 1100 x 600 mm (W x H x D)

Paintwork:

Powder coating

Colour:

Body: RAL 7035, light grey

Base, worktop and design elements:

RAL 7043, traffic grey B

Protection class:

IP 65 for door

Base cabinet

RIW 2 Standard version

Order No. 38.03 02 01



Worktop



Door at the front



Base



Locking system



2 fixed shelves

RIW Industrial Workstation

Base cabinet design variations

RIW 2 Special version according to specification

Order No. **38.03 99 99 8**



Door at the front, door at the back



Individual dimensions



Base:
Base with height of 100mm
4 steerable wheels



Mounting plate



Pull-out tray



Locking systems:
Triangular
Square
Double ward
Lock cylinder

Construction

Commander



ComTronic



SL 2000



SL 3000



SL 4000

Connection



GTK electronic / GTN II / GT 48/2:
Base with connecting tube and
coupling



Foot stand turnable



Inclining adapter



Moterm inclining adapter



Foot stand turnable
with adapter plate

Base cabinet



Company _____ Phone _____

Contact _____ Fax _____

Address _____ E-mail _____

Base cabinet

- Standard version Special version

Dimensions (L x W x H) _____ x _____ x _____ mm

- Colour** Standard: Middle section RAL 7035, side strips / worktop RAL 7043
 Special colours (please specify individually as RAL colours)

Middle section: RAL _____ Side strips: RAL _____ Work plate: RAL _____


- Door** Door at the front, door at the back Door at the front, screwed rear panel

- Base** Base, 100 mm in height Base, individual height _____ mm

- Lock types** Triangular Double ward
 Square Lock cylinder with key
 Others _____

- Accessories** A3 Wiring diagram pocket Fixed shelf
 Pull-out shelf Mounting plate
 Flange plate with sealing membrane Interior light with door switch
 Filter fan Outlet filter

Number _____ Number _____
 Side C Side D Side C Side D



Commander systems

- ComTronic SL 2000 SL 3000 SL 4000

Connection systems

- GTK electronic: foot stand, tube, coupling tube length _____ mm
 GT 48/2: foot stand, tube, flange coupling tube length _____ mm
 GTN II: foot stand, tube, coupling tube length _____ mm
 GTN II: foot stand turnable
 GTN II: foot stand turnable with adapter plate
 Moterm inclining adjustment
 GTN II inclining adapter
 GT 48/2 and GTK electronic inclining adapter